2019 Subaru WRX®

Specifications

Engine				ocharged/intercooled, aluminum	
Displacement		cylinder heads and l 1,998 cc	DIOCK		
Displacement Bore x Stroke		86 mm x 86 mm			
Compression ratio		10.6:1			
•					
Horsepower		268@5,600 rpm			
Torque lb-ft		258@2,000-5,200 rpm			
Valvetrain		Chain driven Double Overhead Camshafts (DOHC), four valves per cylinder, Subaru Dual Active Valve Control System (AVCS) variable valve timing on intake and exhaust valves			
Fuel / Induction		Gasoline Direct Injection (GDI), Electronic Throttle Control (ETC), twin-scroll turbocharger with intercooler			
Maximum boost		15.9 PSI			
Fuel requirement		91 AKI required			
Drivetrain		-			
Transmission		Standard: 6-speed manual Optional: Sport Lineartronic™ CVT features SI-DRIVE performance management with 6-speed and 8-speed manual shifting modes and steering wheel paddle shift switches			
M/T AWD system		Continuous All-Wheel Drive with viscous-coupling locking center differential and nominal 50:50 torque split; transfers more torque to wheels with best traction			
A/T AWD system		Variable Torque Distribution (VTD) with planetary gear-type center differential and an electronically controlled hydraulic transfer clutch, 45:55 nominal torque split; transfers more torque to wheels with best traction			
Transmission ratios		6-speed manual Sport Lineartronic™ CVT			
		•	6 ratios (Intelligent and Sport modes)	8 ratios (Sport Sharp mode)	
	1	3.454	3.505	3.505	
	2	1.947	2.238	2.405	
	3	1.296	1.641	1.855	
	4	0.972	1.194	1.544	
	5	0.780	0.880	1.258	
	6	0.666	0.611	1.032	
	7			0.856	
	8			0.716	
	R	3.636		2.345	
Final drive ratio		4.111		3.900	
Stability/traction control		Vehicle Dynamics Control with all-wheel, all-speed traction control and Active Torque Vectoring			
Chassis		Unitized body construction, Ring-Shaped Reinforcement Frame safety structure			
Suspension		4-wheel independent; sport-tuned plus special chassis reinforcements			
	Front MacPherson-type struts (inverted struts for Premium and Limited) aluminum lower L-arms with pillow ball mounts and bushings, coil springs and stabilizer bar				
	Rear	Double wishbone w springs and stabiliz		shings for lower lateral links, coil	

Brakes	Power-assisted 4-wheel disc with Electronic Brake-force Distribution (EBD) and			
	4-channel / 4-sensor ABS, Brake Assist and Brake Override (plus switch-			
	activated Electronic Parking Brake and Auto Vehicle Hold with EyeSight option)			
Front	·			
Rear	11.3-inch solid discs, single-piston calipers (11.8-inch with EyeSight option)			
Steering	Rack-and-pinion with electric power assist			
Ratio	Base: 14.3:1			
	Premium, Limited and Series.Gray: 14.4:1			
Turns, lock-to-lock				
Trumina sinala	Premium, Limited and Series.Gray: 2.7 Base: 35.4 ft			
Turning circle	Premium, Limited and Series.Gray: 36.0 ft			
Wheels	WRX			
VVIICEIS	17 x 8-inch aluminum alloy in dark gray finish			
	WRX Premium and Limited			
	18 x 8.5-inch aluminum alloy in dark gray finish			
	WRX Series.Gray			
	18 x 8.5-inch aluminum alloy in black finish			
Tires	WRX			
	235/45R17 94W summer performance			
	MDVD : It is a constant			
	WRX Premium, Limited and Series.Gray			
Exterior Dimensions	245/40R18 97W summer performance			
(in.)				
Wheelbase	104.3			
Length	180.9			
Height	58.1			
Width	70.7			
Track (front /rear)	60.2 in. / 60.6 in.			
Road clearance	4.9 in.			
	WRX: 3,294			
Base curb weight (lb.)	WRX. 3,294 WRX Premium: 3,336			
	WRX Series.Gray: 3,340			
	WRX Limited: 3,371WRX Premium with Sport Lineartronic™ CVT: 3,488			
	WRX Limited with Sport Lineartronic™ CVT: 3,512			
Interior Dimensions				
(in.)				
Headroom	Front: 39.8 With moonroof: 37.2			
1	Rear: 37.1			
Legroom	Front: 43.3 Rear: 35.4			
Hip room	Front: 52.1 Rear: 53.1			
Shoulder room	Front: 55.6 Rear: 54.2			
EPA passenger	96.6 cu. ft. With moonroof: 93.1 cu. ft.			
volume	40.0			
Trunk capacity	12.0 cu. ft.			
Trunk liftover height	27.0			
EPA	6-speed manual: 21/27/23 Sport Lineartronic® CVT: 18/24/21			
City/highway/combined				
	45.0			
Fuel capacity	15.9 gal.			