2012 Subaru Impreza 2.0i Specifications

Engine			
Туре	4-cyl., horizontally opposed (Boxer), alloy cylinder block and cylinder heads		
Displacement	1,995 cc / 122 cu. in.		
Bore x stroke	3.31 in. x 3.54 in.		
Compression ratio	10.5:1		
Horsepower	148 @ 6,200 rpm		
Torque	145 lbft. @ 4,200 rpm		
Fuel system	Sequential multi-port fuel injection, electronic throttle control		
Valvetrain	Double overhead chain-driven camshafts (DOHC), 4 valves per cylinder, dual Active Valve Control System (DAVCS) controls valve timing on intake and exhaust camshafts; tumble generator valves		
Ignition	Direct type with platinum-tipped sparkplugs		
Transmission			
Standard	5-speed manual with Incline Start Assist		
Optional	Lineartronic® CVT (continuously variable transmission). Standard for Limited models. On Premium, Sport and Limited models, features driver-selectable 6-speed manual shift mode and steering wheel shift paddles		
Transmission ratios	5-speed manual	CVT paddle shift ratios	
1	3.454	3.581	
2	1.888	2.262	
3	1.296	1.658	
4	0.972	1.208	
5	0.738	0.850	
6		0.570	
R	3.333	3.667	
Final drive	4.11	3.70	
Symmetrical All-Wheel Drive	Standard on all models		
M/T AWD system	Continuous All-Wheel Drive with viscous-coupling locking center differential		
CVT AWD system	Active All-Wheel Drive with electronically managed continuously variable hydraulic transfer clutch		
Stability/traction control	Vehicle Dynamics Control with all-wheel, all-speed traction control		

Chassis	Unitized body construction, F	Ring Shaped Frame	
	Reinforcement safety structure		
Suspension	4-wheel independent		
Front	MacPherson-type struts, lower L-arms, coil springs, stabilizer		
	bar		
Rear	Double wishbone, coil springs; Premium, Sport and Limited		
	models add stabilizer bar		
Brakes	Power-assisted 4-wheel disc with Electronic Brake-force		
	Distribution (EBD) and 4-channel / 4-sensor ABS and Brake		
	Assist; 10.9-in. ventilated front discs and 10.8-in. solid rear		
	discs; Brake override system		
Steering	Rack-and-pinion with electric power assist		
	Turns, lock-to-lock: 3.2 Turning circle: 34.8 ft.		
Wheels	Base: 15 x 6-in. steel with full wheel covers Premium: 16 x 6.5 in. aluminum alloy Sport and Limited (opt. for Premium): 17 x 7 aluminum alloy		
Tine			
Tires	Base: 195/65R15		
	Premium: 205/55R16		
Exterior Dimensions (in)	Sport and Limited and opt. for Premium: 205/50R17		
Exterior Dimensions (in.)	4 door: 0.31		
Coefficient of drag (Cd) Wheelbase	4-door: 0.31 5-door: 0.33		
	104.1		
Length	4-door: 180.3		
Width	5-door: 173.8 68.5 (78.2 inc. mirrors)		
Height	57.7 (59.5 for 5-door with roof rails)		
Track (front/rear)	57.7 (59.5 for 5-door with root rails) 59.4/59.6		
Curb weight (lbs.)	5-speed manual	CVT	
4-door	Base: 2,910	Base: 2,976	
4-4001	Premium: 2,954	Premium: 3,009	
		Limited: 3,053	
5-door	Base: 2,910	Base: 2,910	
3-4001	Premium: 2,954	Premium: 3,009	
	Sport Premium: 2,998	Limited: 3,053	
	2,500	Sport Premium: 3,075	
		Sport Limited: 3,086	
Interior Dimensions (in.)		,	
Headroom (f/r)	39.8/37.1 With moonroof: 37.2/37.1		
Legroom (f/r)	43.5/35.4		
Hip room (f/r)	52.2/53.1		
Shoulder room (f/r)	55.6/54.2		
EPA interior volume	4-door: 96.9 (with moonroof: 93.4)		
(cu. ft.)	5-door: 97.5 (with moonroof: 94.0)		
Trunk liftover height	27.0		
EPA trunk volume, 4-door	12.0 cu. ft.		
Cargo volume, 5-door	Rear seats up/down: 22.5 cu. ft./52.4 cu. ft.		
Max. load floor length, 5-door	Rear seats up/down: 32.0/64.2 in.		
Fuel economy, mpg			
Transmission	5-speed manual	CVT	
EPA city/highway/combined	25/34/28 (25/33/28 for 5-doc	or) 27/36/30 (all models)	
Fuel tank capacity	14.5 gal.		