2022 Subaru Outback® Wilderness

Specifications

Vehicle type	5-passenger sport utility vehicle with enhanced off-pavement capability
Engine	DOHC 4-cylinder BOXER; aluminum cylinder block and heads; turbocharged
Bore x Stroke	94 x 86mm (3.70 x 3.39 in.)
Displacement	2,387cc (146 cu. in.)
Compression ratio	10.6:1
Valvetrain	Chain-driven camshafts, Dual Active Valve Control System (intake and exhaust valves)
Fuel/induction	Direct Fuel Injection and Electronic Throttle Control (ETC) system; twin- scroll turbocharger, intercooler
Max. boost pressure	14.5 psi
Horsepower	260 hp @ 5,600 rpm
Torque	277 lb-ft @ 2,000-4,800 rpm
Fuel requirement	Regular grade, 87 AKI minimum
Ignition system	Direct
Drivetrain	
Transmission	High-torque Lineartronic® CVT includes 8-speed manual mode and steering wheel paddle shift switches; revised lower ratios exclusive to Wilderness model
Ratios, manual mode 1 2 3 4 5 6 7 8 R	3.490 2.497 1.788 1.381 1.065 0.830 0.653 0.506 3.394
Final drive	4.44:1

Symmetrical AWD	Active Torque Split AWD with electronically managed variable hydraulic transfer clutch; continuously varies front-to-rear torque split based on inputs from acceleration, steering angle and yaw rate sensors; can proactively transfer more torque to rear wheels or in response to wheel slip.
	Exclusive to Wilderness model: advanced X-Mode system optimizes engine output and CVT ratio position, increases Active All-Wheel Drive engagement and uses enhanced control logic for the Vehicle Dynamics Control (VDC) system to reduce individual wheel spin to offer even more capability and control on slippery road surfaces and inclines; features Snow/Dirt mode, Deep Snow/Mud mode (under 25 mph); Deep Snow/Mud mode (above 25 mph); Low Speed / Low Ratio Gradient Control can automatically detect vehicle travel on steep gradients and shift to a CVT low ratio comprised of a lower transfer gear ratio and lower first ratio.
Dynamic controls	Vehicle Dynamics Control (VDC) with electronic traction control (TCS); Active Torque Vectoring (using brakes); Auto Vehicle Hold (AVH), Hill Descent Control (HDC)
Chassis	Unitized body construction, Ring-shaped Frame Reinforcement safety structure
Suspension	4-wheel independent, raised with exclusive Wilderness specifications for 0.8-in. increase in road clearance than other Outback models
Front	MacPherson-type struts with internal rebound springs, aluminum lower L-arms, coil springs and stabilizer bar, liquid filled engine mounts
Rear	Double wishbone, coil springs and stabilizer bar
Steering	Electric power-assisted rack-and-pinion, variable gear ratio rack Ratio: 13.5:1 Turns lock-to-lock: 2.7 Turning circle, curb to curb: 36.1 ft.
Brakes	Power-assisted 4-wheel disc with Electronic Brake-force Distribution (EBD), 4-channel / 4-sensor ABS, Brake Assist, Brake Override and Auto Vehicle Hold (AVH) Front: 12.4-in. ventilated rotors, dual-piston calipers Rear: 11.8-in. ventilated rotors, single-piston calipers
Wheels	17 x 7-in. alloy, matte black finish
Tires	Yokohama Geolandar A/T 225/65 R17 102T all-season, raised white letter
Exterior Dimensions	
Wheelbase	108.1 in.
Length	191.3 in.
Height	Including roof rails: 66.9 in.
Width	74.6 in. / 82.0 in. with mirrors
Track (f/r)	62.0 in. / 63.0 in.
Min. road clearance	9.5 in. (0.8-in. increase over other Outback models)

Overhang (f/r)	39.6 in. / 43.7 in.
Angle of approach	20.0 deg.
Angle of departure	23.6 deg.
Breakover angle	21.2 deg.
Curb weight	3,896 lbs. (3,929 lbs. with option package that adds navigation, moonroof and Reverse Automatic Braking)
Towing capacity	3,500 lbs. with 350-lb. trailer tongue weight
Interior Dimensions	
Head room (f/r)	40.1 in. / 39.1 in. With moonroof: 37.7 in. / 39.1 in.
Leg room (f/r)	42.8 in. / 39.5 in.
Hip room (f/r)	55.5 in. / 54.8 in.
Shoulder room (f/r)	58.1 in. / 57.4 in.
EPA passenger volume	109.0 cu. Ft. With moonroof: 105.6 cu. ft.
EPA cargo volume	32.5 cu. ft. (seatbacks raised) 75.7 cu. ft (seatbacks folded)
Max. cargo length	42.0 in. (seatbacks raised) 75.0 in. (seatbacks folded)
Cargo width between wheel housings	43.3 in.
Cargo area height	32.1 in.
Rear gate opening width	Lower: 44.1 in. Max. 45.2 in.
Rear gate opening height	29.5 in.
Cargo area liftover height	29.2 in.
EPA total interior volume	141.5 cu. ft. With moonroof: 138.1 cu. ft.
Fuel Economy	
EPA estimated city / highway / combined mpg	22/26/24
Fuel capacity	18.5 gal.
·	