2022 Subaru Crosstrek

Specifications

Vehicle type	5-do	or, 5-passenger spor	rt-utility	vehicle	
Engine	Base and Premiu			nd Limited	
Displacement	1,995 cc / 122 cu.			/ 152.0 cu. in.	
Bore x Stroke	84.0mm x 90.0 m			x 90.0mm	
Boro x Guoko	(3.31 in. x 3.54 in.			n. x 3.54 in.)	
Compression ratio	12.5:1	,	12.0:1	,	
Horsepower	152 @ 6,000 rpm	1	182 @ 5	5,800 rpm	
Torque	145 lbft. @ 4,000 rpm		t. @ 4,400 rpm		
Fuel system	Direct fuel injection, electronic throttle control				
Fuel requirement	Regular / 87 AKI				
Valvetrain	Double overhead chain-driven camshafts (DOHC), 4 valves per cylinder, Dual Active Valve Control System (DAVCS) controls valve timing on intake camshafts; tumble generator valves				
Ignition	Direct				
Powertrain management	Models equipped with Lineartronic® CVT (continuously variable transmission) include Auto Stop-Start system fuel-saving technology and Subaru SI-DRIVE driver-selectable powertrain management system with Intelligent and Sport modes and steering wheel control switches.				
Transmission					
Standard for Base and Premium	6-speed manual with Incline Start Assist				
Standard for Sport and Limited; optional for Base and Premium	 Lineartronic® CVT with Incline Start Assist Premium, Sport and Limited feature driver-selectable 8-speed manual shift mode and steering wheel paddle shift control switches Base trim has Low Shift Mode Premium and Limited have X-MODE and Hill Descent Control Sport has Dual-mode X-Mode with SNOW/DIRT and DEEP SNOW/MODE selectable settings 				
Transmission ratios	6-speed manual	2.0-liter engine (ratios (manual co mode)		2.5-liter engine CVT ratios (manual control mode)	
1	3.818	4.066		4.066	
2	1.947	2.600		2.628	
3	1.296	1.827		1.911	
4	1.029	1.377		1.490	
5	0.825	1.061		1.166	
6	0.738	0.836		0.914	
7		0.668		0.717	
8		0.559		0.559	
R	4.073	4.379		4.379	
Final drive	4.444	3.900		3.700	
Symmetrical All-Wheel Drive	Standard on all models				
M/T AWD system	Continuous All-Wheel Drive with viscous-coupling locking center differential				
CVT AWD system	Active Torque Split All-Wheel Drive with electronically controlled variable hydraulic transfer clutch				

Stability/traction control	Vehicle Dynamics Control with all-wheel, all-speed traction control (TCS) and rollover sensor				
Chassis		Unitized body construction, Ring-shaped Reinforcement Frame			
Onassis	safety structure				
Suspension	4-wheel independent, raised				
Front	MacPherson-type struts, lower L-arms, coil springs, Stablex				
	dampers, stabilizer bar				
	Hydraulic engine mounts on CVT models				
Rear	Double wishbone, coil springs, Stablex dampers, stabilizer bar				
Brakes	Power-assisted 4-wheel disc with Electronic Brake-force Distribution				
	(EBD) and 4-channel / 4-sensor ABS with Brake Assist and Brake				
	Override safety systems and Active Torque Vectoring				
	11.6-in. ventilated front discs and 10.8-in. solid rear discs				
Steering	Rack-and-pinion with electric power assist				
	Ratio: 13:1				
	Turns, lock-to-lock: 2.6				
	Turning circle: 35.4 ft.				
Wheels	Base, Premium and Sport: 17 x 7-in. aluminum alloy				
	Limited: 18 x 7-in. aluminum alloy				
Tires	Base, Premium and Sport: 225/60R17 98H all-season				
	Limited: 225/55R18 98H all-season				
Exterior Dimensions					
Wheelbase	104.9 in.				
Length	176.5 in.				
Width	71.0 in. (79.0 in. including mirrors)				
Height	63.6 in. with roof rails				
Min. road clearance	8.7 in.				
Angle of approach	18.0 deg.				
Angle of departure	28.6 deg.				
Ramp breakover angle	19.7 deg.				
Track (front/rear)	61.0/61.2 in.				
Curb weight (lbs.)	Base w/ 6-speed manual: 3,117				
	Base w/CVT: 3,188				
	Premium w/6-speed manual: 3,146				
	Premium w/ CVT: 3,223				
	Sport (CVT only): 3,265				
	Limited (CVT only): 3,298				
Interior Dimensions					
Headroom (f/r)	39.8/38.0 in. with moonroof: 37.6 /37.8 in.				
Legroom (f/r)	43.1/36.5 in.				
Hip room (f/r)	55.1/55.2 in.				
Shoulder room (f/r)	56.7/55.6 in.				
EPA interior volume	100.9 cu. ft. with moonroof: 97.5 cu. ft.				
Cargo liftover height	30.9 in.				
Cargo volume	Rear seats up/down: 20.8 cu. ft./55.3 cu. ft.				
Max. load floor length	Rear seats up/down: 32.3/64.2 in.				
Fuel economy	6-speed manual	2.0-liter with CVT	2.5-liter with CVT		
EPA-estimated	22/29/25	28/33/30	27/34/29		
city/highway/combined					
mpg					
Fuel tank capacity	16.6 gal. (all)				