## 2023 Subaru BRZ

## Specifications

Vehicle type	2+2 sports car with aluminum hood, front fenders and roof		
Engine	FA24 4-cylinder, horizontally opposed (SUBARU BOXER), aluminum alloy cylinder block and cylinder heads		
Displacement	2,387 cc (146 cu. in.)		
Bore x Stroke	94 mm x 86 mm (3.70 x 3.39 in.)		
Compression ratio	12.5:1		
Fuel/Induction	Direct and port fuel injection with multi-spray injectors, Electronic Throttle Control system		
Horsepower	228 @ 7,000 rpm		
Torque	184 lbft. @ 3,700 rpm		
Valvetrain	Chain driven double overhead camshafts (DOHC), four valves per cylinder, Subaru Dual Active Valve Control System variable valve timing on intake and exhaust camshafts.		
Fuel requirement	Premium, 93 AKI		
Ignition	Direct		
Drivetrain	Rear-wheel drive with TORSEN® limited-slip differential		
Transmission type	Standard: 6-speed manual Optional: 6-speed automatic with Adaptive Control, manual shift mode, downshift blipping control and steering wheel paddle shift control switches		
Stability/traction control	Vehicle Stability Control (VSC) with traction control system (TCS); multi-mode switch with Track mode and TCS Off switch		
Transmission ratios	6-speed manual	6-speed automatic	
1	3.626	3.538	
2	2.189	2.060	
3	1.541	1.405	
4	1.213	1.000	
5	1.000	0.713	
6	0.767	0.582	
R	3.438	3.168	
Final drive ratio	4.100	3.909	
Chassis	Unitized body construction with Ring-shaped Frame Reinforcement structure		
Center of gravity	17.95 in.		
Suspension	4-wheel independent		
Front	MacPherson-type struts; lower L-arms, coil springs, stabilizer bar, strut tower brace and anti-dive geometry		
Rear	Double-wishbone type with coil springs, stabilizer bar and anti-lift geometry		
Brakes	4-wheel disc with Electric vacuum pump power assist 4-channel / 4-sensor ABS, Electronic Brake-force Distribution and Brake Assist		
Front	11.6 in. ventilated disc, dual-piston calipers		
Rear	Limited: 11.4 in. ventilated disc, single-piston calipers		
Steering	Quick-ratio rack-and-pinion with electric power assist		
Ratio	13.5:1		
Turns, lock-to-lock	2.5		
Turning circle	35.4 ft.		

	1
Premium: 17 in. x 7.5 in. aluminum alloy, high-luster gray finish	
Limited: 18 in. x 7.5 in. aluminum alloy, matte dark gray finish	
Premium: 215/45 R17 87W summer performance	
Limited: 215/40 R18 85Y Michelin Pilot Sport 4 summer performance	
All models feature tire repair kit	
101.4 in.	
167.9 in.	
69.9 in	
51.6 in.	
59.8 in./61.0 in.	
5.1 in.	
6-speed manual	6-speed automatic
Premium: 2,815	Premium: 2,835
Limited: 2,864	Limited: 2,881
37.0 in. / 33.5 in.	
41.5 in. / 29.9 in.	
52.4 in. / 45.2 in.	
53.6 in. / 51.7 in.	
77.2 cu. ft.	
6.3 cu. ft. (additional carrying space with rear seatback folded)	
27.1 in.	
6-speed manual: 20/27/22 MPG	
6-speed automatic: 21/30/25 MPG	
13.2 gal	
	Limited: 18 in. x 7.5 in. aluminum alloy, r Premium: 215/45 R17 87W summer perfor Limited: 215/40 R18 85Y Michelin Pilot S All models feature tire repair kit 101.4 in. 167.9 in. 69.9 in 51.6 in. 59.8 in./61.0 in. 5.1 in. 6-speed manual Premium: 2,815 Limited: 2,864 37.0 in. / 33.5 in. 41.5 in. / 29.9 in. 52.4 in. / 45.2 in. 53.6 in. / 51.7 in. 77.2 cu. ft. 6.3 cu. ft. (additional carrying space with reconstruction of the construction of the constr