## 2013 Subaru XV Crosstrek

## Specifications

Vehicle type	5-door, 5-passenger crossover		
Engine	4-cyl. horizontally opposed (Boxer), alloy cylinder block and		
	cylinder heads		
Displacement	1,995 cc / 122 cu. in.		
Bore x stroke	3.31 in. x 3.54 in.		
Compression ratio	10.5:1		
Horsepower	148 @ 6,200 rpm		
Torque	145 lbft. @ 4,200 rpm		
Fuel system	Sequential multi-port fuel injection, electronic throttle control		
Valvetrain	Double overhead chain-driven camshafts (DOHC), 4 valves per		
	cylinder, Dual Active Valve Control System (DAVCS) controls		
	valve timing on intake camshafts; tumble generator valves		
Ignition	Direct type with platinum-tipped sparkplugs		
Transmission	• • • • • • •		
Standard	5-speed manual with incline start assist		
Optional	Lineartronic® CVT (continuously variable transmission).		
		Features driver-selectable 6-speed	
	manual shift mode and steering wheel shift paddles; incline start assist		
Transmission ratios	5-speed manual	CVT paddle shift ratios (for	
	·	manual control mode)	
1	3.545	3.581	
2	1.888	2.262	
3	1.296	1.658	
4	0.972	1.208	
5	0.780	0.885	
6		0.618	
Rev.	3.333	3.667	
Final drive	4.444	3.70	
Symmetrical All-Wheel	Standard all models		
Drive			
M/T AWD system	Continuous All-Wheel Drive with viscous-coupling locking center differential		
CVT AWD system	Active Torque Split All-Wheel Drive with electronically managed		
continuously variable hyd			
Stability/traction control	Vehicle Dynamics Control with all-wheel, all-speed traction		
_	control (TCS) and rollover sensor		
Chassis	Unitized body construction	itized body construction, Ring Shaped Frame Reinforcement	
	safety structure		
Suspension	4-wheel independent, raised		
Front	MacPherson-type struts, lower L-arms, coil springs, stabilizer		
	bar Hydraulic engine mounts on CVT models.		
Rear	Double wishbone, coil springs, stabilizer bar		
Brakes	Power-assisted 4-wheel disc with Electronic Brake-force Distribution (EBD) and 4-channel / 4-sensor ABS with Brake		
	Assist and Brake Override safety systems		
11.6-in. ventilated front discs and 10.8-in. solid rear discs			
Steering	Rack-and-pinion with electric power assist		
Turns, lock-to-lock: 3.2			

	Turning circle: 34.8 ft.		
Wheels	17 x 7 aluminum alloy		
Tires	225/55R17 95H all-season		
Exterior Dimensions			
Wheelbase	103.7 in.		
Length	175.2 in.		
Width	70.1 in. (78.2 in. inc. mirrors)		
Height	63.6 in. with roof rails		
Ground clearance	8.7 in.		
Angle of approach	18.0 deg.		
Angle of departure	27.7 deg.		
Ramp breakover angle	21.1 deg.		
Track (front/rear)	60.0/60.0 in.		
Curb weight (lbs.)	2.0i Premium	2.0i Limited	
	5-speed manual: 3,087	3,164 (CVT only)	
	Lineartronic CVT: 3,142	With all options: 3,197	
	With all options: 3,175		
Interior Dimensions			
Headroom (f/r)	39.8/37.7 in. With moonroof: 37.2/37.7 in.		
Legroom (f/r)	43.5/35.4 in.		
Hip room (f/r)	52.2/53.1 in.		
Shoulder room (f/r)	55.6/54.2 in.		
EPA interior volume	97.5 cu. ft. (with moonroof: 94.0)		
Trunk liftover height	27.8. in.		
Cargo volume	Rear seats up/down: 22.3 cu. ft./51.9 cu. ft.		
Max. load floor length	Rear seats up/down: 32.0/64.2 in.		
Fuel economy	5-speed manual	CVT	
Projected	23/30/26	25/33/28	
city/highway/combined			
mpg			
Fuel tank capacity	15.9 gal.		