## 2024 Subaru Crosstrek

Specifications

Vehicle type	5-door, 5-passenger sport-utility vehicle			
Engine	Base and Premium	Sport, Limited, Wilderness		
Type	SUBARU BOXER four-	SUBARU BOXER four-		
	cylinder, aluminum cylinder	er cylinder, aluminum cylinder		
	block and cylinder heads	block and cylinder heads		
Displacement	1,995 cc / 122 cu. in.	2,498cc / 152.0 cu. in.		
Bore x Stroke	84.0mm x 90.0mm	94.0mm x 90.0mm		
	(3.31 in. x 3.54 in.)	(3.70 in. x 3.54 in.)		
Compression ratio	12.5:1	12.0:1		
Horsepower	152 @ 6,000 rpm	182 @ 5,800 rpm		
Torque	145 lbft. @ 4,000 rpm			
Fuel system	Direct fuel injection, electronic throttle control			
Fuel requirement	Regular / 87 AKI			
Valvetrain	Double overhead chain-driven camshafts (DOHC), 4 valves per			
varvotram	cylinder, Dual Active Valve Control System (DAVCS) controls valve			
	timing on intake camshafts; tumble generator valves			
Ignition	Direct			
Powertrain management				
1 owertrain management	, , ,			
	Subaru SI-DRIVE driver-selectable powertrain management     system with Intelligent and Sport modes and steering wheel			
	system with Intelligent and Sport modes and steering wheel			
Transmission	control switches.			
Transmission	Lineartronic® CVT with Incline Start Assist			
	Base trim has low shift mode			
	Premium, Sport, Wilderness and Limited feature driver-			
	selectable 8-speed manual shift mode and steering wheel			
	paddle shift control switches			
	Base, Premium have X-MODE and Hill Descent Control			
	Sport and Wilderness and Limited have Dual-function X-MODE			
	with SNOW/DIRT and DEEP SNOW/MODE selectable settings			
	<u>.</u>	oled transmission fluid cooler		
Transmission ratios	2.0-liter engine CVT	2.5-liter engine CVT ratios (manual		
	ratios (manual	control mode)		
	control mode)			
1	4.066	4.066		
2	2.628	2.646		
3	1.911	1.965		
4	1.535	1.532		
5	1.195	1.199		
6	0.914	0.939		
7	0.717	0.729		
8	0.559	0.559		
R	4.379	4.379		
Final drive	3.900	3.700 (Wilderness: 4.111)		
Symmetrical All-Wheel	Standard on all models: ACT-4 Active Torque Split All-Wheel Drive			
Drive	with electronically controlled variable hydraulic transfer clutch			
Stability/traction control	Vehicle Dynamics Control with all-wheel, all-speed traction control			
Stability/tradition don't don't do	(TCS) and rollover sensor			
Chassis	Unitized body construction, full inner frame safety structure			
Suspension	4-wheel independent, raised			
Guaperiaiori	т мностинарениети, газеч			

Front	MacPherson-type struts, lower L-arms, coil springs, dampers,				
Door	stabilizer bar, hydraulic engine mounts				
Rear	Double wishbone, coil springs, dampers, stabilizer bar				
Brakes	Electronic Brake-force Distribution (EBD), 4- channel / 4-sensor ABS, Brake Assist, Brake Override, Auto Vehicle Hold (AVH) and				
	Active Torque Vectoring				
	Front: 12.4-in. ventilated discs with dual-piston calipers Rear: 11.2-in. ventilated discs with single-piston calipers				
Steering	Dual Pinion Electric Power Assisted Steering (EPAS) Ratio: 13.0:1				
Steering					
	Turns, lock-to-lock: 2.5				
	Turning circle: 35.44 ft. (Wilderness: 34.78 ft.)				
Wheels	Base and Premium: 17 x 7-in. aluminum alloy				
VVIICCIS	Sport and Limited: 18 x 7-in. aluminum alloy				
	Wilderness: 17 x 7-in. aluminum alloy, matte black finish				
Tires	2.0L Base and Premium: 225/60R17 99H all-season				
11100		2.5L Sport and Limited: 225/55R18 98V all-season			
	2.5L Wilderness: 225/60R17 99T all-terrain				
Exterior Dimensions	Base, Premium, Sport and	Wilderness			
Exterior Difficusions	Limited	· · · · · · · · · · · · · · · · · · ·			
Wheelbase	105.1 in.	104.9 in.			
Length	176.4 in.	176.4			
Width	70.9 in. (79.4 in. including	71.7 (79.4 including mirrors)			
771001	mirrors)	(			
Height	63.0 (62.8 for Base)	63.6			
Min. road clearance	8.7 in.	9.3			
Angle of approach	18.0 deg.	20.0 deg.			
Angle of departure	30.1 deg.	33.0 deg.			
Ramp breakover angle	19.7 deg.	21.1 deg.			
Track (front/rear)	61.2/61.2 in.	60.9/60.8 in.			
Curb weight (lbs.)	Base: 3,277				
, ,	Premium: 3,296 (3,333 with option	ons)			
	Sport: 3,332 (3,368 with options)				
	Limited: 3,349 (3,391 with options)				
	Wilderness: 3,369 (3,417 with op	tions)			
Towing capacity	1,500 lbs. (class 1); 400-lb	3,500 lbs. (class 1); 400-lb			
	tongue weight	tongue weight			
Crossbar dynamic load	Base: 176				
capacity (lbs.)	Premium, Sport, Wilderness and	Limited: 165			
Crossbar static load	Premium, Sport, Wilderness and Limited: 700				
capacity (lbs.)					
Interior Dimensions					
Headroom (f/r)	39.8/38.0 in. With moonroof: 38	.7/38.0 in.			
Legroom (f/r)	42.9/36.5 in.				
Hip room (f/r)	55.1/53.2 in.				
Shoulder room (f/r)	56.8/55.3 in.				
EPA interior volume	100.5 cu. ft. With moonroof: 99.0 cu. ft.				
Cargo area height	29.3 in.	29.4 in.			
Cargo liftover height	30.7 in.	31.3 in.			
Cargo volume	Rear seats up/down: 19.9/54.7	20.0/54.9 cu. ft.			
	cu. ft.				
Max. load floor length	Rear seats up/down: 32.1/63.9 in	l			

Fuel economy	2.0L Base and	2.5L Sport and	2.5L Wilderness
	Premium	Limited	
EPA-estimated city/highway/combined mpg	27/34/29	26/33/29	25/29/27
Fuel tank capacity	16.6 gal. (all)		