2015 Subaru XV Crosstrek

Specifications

Vehicle type	5-door, 5-passenger crossover		
Engine	4-cyl. horizontally opposed (Boxer), alloy cylinder block and		
-	cylinder heads		
Displacement	1,995 cc / 122 cu. in.		
Bore x stroke	3.31 in. x 3.54 in.		
Compression ratio	10.5:1		
Horsepower	148 @ 6,200 rpm		
Torque	145 lbft. @ 4,200 rpm		
Fuel system	Sequential multi-port fuel injection, electronic throttle control		
Valvetrain	Double overhead chain-driven camshafts (DOHC), 4 valves per cylinder, Dual Active Valve Control System (DAVCS) controls valve timing on intake camshafts; tumble generator valves		
Ignition	Direct type with platinum-tipped sparkplugs		
Transmission	Diroci type with platinum-upped sparkplugs		
	E an a dim annual suith la ali	a Otart Assist	
Standard	5-speed manual with Incline Start Assist		
Optional	Lineartronic [®] CVT (continuously variable transmission). (Standard for Limited.) Features driver-selectable 6-speed manual shift mode and steering wheel shift paddles; incline start assist		
Transmission ratios	5-speed manual	CVT paddle shift ratios (for manual control mode)	
1	3.545	3.581	
2	1.888	2.262	
3	1.296	1.658	
4	0.972	1.208	
5	0.780	0.885	
6		0.618	
Rev.	3.333	3.667	
Final drive	4.444	3.700	
Symmetrical All-Wheel Drive	Standard all models		
M/T AWD system	Continuous All-Wheel Drive with viscous-coupling locking center differential		
CVT AWD system	Active Torque Split All-Wheel Drive with electronically managed continuously variable hydraulic transfer clutch		
Stability/traction control	Vehicle Dynamics Control with all-wheel, all-speed traction control (TCS) and rollover sensor		
Chassis	Unitized body construction, Ring Shaped Frame Reinforcement safety structure		
Suspension	4-wheel independent, rais	ed	
Front	MacPherson-type struts, lower L-arms, coil springs, stabilizer bar Hydraulic engine mounts on CVT models.		
Rear	Double wishbone, coil springs, stabilizer bar		
Brakes	Power-assisted 4-wheel disc with Electronic Brake-force Distribution (EBD) and 4-channel / 4-sensor ABS with Brake Assist and Brake Override safety systems 11.6-in. ventilated front discs and 10.8-in. solid rear discs		
Steering	Rack-and-pinion with electric power assist Ratio: 14:1		

	Turns, lock-to-lock: 2.8		
	Turning circle: 34.8 ft.		
Wheels	17 x 7 aluminum alloy		
Tires	225/55R17 95H all-season		
Exterior Dimensions			
Wheelbase	103.7 in.		
Length	175.2 in.		
Width	70.1 in. (78.2 in. inc. mirrors)		
Height	63.6 in. with roof rails		
Ground clearance	8.7 in. at front crossmember		
Angle of approach	18.0 deg.		
Angle of departure	27.7 deg.		
Ramp breakover angle	21.1 deg.		
Track (front/rear)	60.0/60.0 in.		
Curb weight (lbs.)	2.0i Premium	2.0i Limited	
	5-speed manual: 3,109 Premium 5-speed: 3,109 Premium CVT: 3,186	3,208 (CVT only)	
Interior Dimensions			
Headroom (f/r)	39.8/37.7 in. With moonroof: 37.2/37.7 in.		
Legroom (f/r)	43.5/35.4 in.		
Hip room (f/r)	52.2/53.1 in.		
Shoulder room (f/r)	55.6/54.2 in.		
EPA interior volume	97.5 cu. ft. (with moonroof: 94.0)		
Trunk liftover height	27.8. in.		
Cargo volume	Rear seats up/down: 22.3 cu. ft./51.9 cu. ft.		
Max. load floor length	Rear seats up/down: 32.0/64.2 in.		
Fuel economy	5-speed manual	CVT	
EPA-estimated	23/31/26	26/34/29	
city/highway/combined			
mpg			
Fuel tank capacity	15.9 gal.		