2016 Subaru Impreza®

Specifications

Engine			
Type	4-cyl. horizontally opposed (Boxer), aluminum cylinder block		
Туре	and cylinder heads		
Displacement	1,995 cc / 122 cu. in.		
Bore x stroke	84 x 90mm		
Compression ratio	10.5:1		
Horsepower	148 @ 6,200 rpm		
Torque	145 lb-ft. @ 4,200 rpm		
Fuel system	Sequential multi-port fuel injection, electronic throttle control		
Valvetrain	Chain driven Double Overhead Camshafts (DOHC); 4 valves		
vaivetiaiii	per cylinder, Dual Active Valve Control System (DAVCS)		
	controls valve timing on intake and exhaust camshafts;		
	tumble generator valves		
Ignition	Direct-ignition system with platinum-tipped sparkplugs		
Drivetrain	Brook ignition dystom with platman appear opartiplage		
Standard	5-speed manual with Incline Start Assist		
Optional	Lineartronic® CVT (continuously variable transmission) is		
Optional	standard for Premium and Limited trims, optional for 2.0i base		
	and Sport Premium. On Premium, Sport Premium, Limited		
	and Sport Limited, the CVT features 6-speed manual shift		
	mode and steering wheel shift paddles		
Transmission ratios	5-speed manual	CVT paddle shift ratios	
1	3.454	3.581	
2	1.888	2.262	
3	1.296	1.658	
4	0.972	1.208	
5	0.738	0.885	
6		0.618	
R	3.333	3.667	
Final drive	4.111	3.700	
Symmetrical All-Wheel Drive	Standard on all models		
M/T AWD system	Continuous All-Wheel Drive with viscous-coupling locking		
-	center differential		
CVT AWD system	Active All-Wheel Drive with electronically controlled variable		
	hydraulic transfer clutch		
Stability/traction system	Vehicle Dynamics Control (VDC) with all-wheel, all-speed		
	traction control		
Chassis	Unitized body construction, Ring-shaped Reinforcement		
	Frame		
Suspension	4-wheel independent		
Front	MacPherson-type struts, lower L-arms, coil springs, stabilizer		
5	bar Davida kara a sail sasis sa a all bat 0 0 i basa basa sa a		
Rear	Double wishbone, coil springs; all but 2.0i base have rear		
Brakes	stabilizer bar Power-assisted 4-wheel disc with Electronic Brake-force		
Diakes	Distribution (EBD) and 4-channel / 4-sensor ABS, Brake		
	Assist and Brake Override systems		
	10.9-in. ventilated front discs and 10.8-in. solid rear discs		
Steering	Quick-ratio rack-and-pinion with electric power assist		
Sieening	Quick-tatio tack-attu-pittiott v	יונוו טופטנווט טטייפו מסטוסנ	

	T		
	Turns, lock-to-lock: 2.9		
	Turning circle: 34.8 ft.		
Wheels	2.0i: 15 x 6-in. steel with full wheel covers		
	Premium: 16 x 6.5-in. aluminum alloy		
	Sport and Limited (opt. for Premium 4-door): 17 x 7-in		
	aluminum alloy		
Tires	2.0i: 195/65R15		
	Premium: 205/55R16		
	Sport and Limited (opt. for Premium 4-door): 205/50R17		
Exterior Dimensions (in.)			
Coefficient of drag (Cd)	4-door: 0.29 5-door: 0.32		
Wheelbase	104.1		
Length	4-door: 180.5		
	5-door: 174.0		
Width	68.5 (78.9 inc. mirrors; 79.5 with turn signal mirrors)		
Height	57.7 (59.4 for 5-door with roof rails)		
Track (front/rear)	59.4/59.6		
Base curb weight (lbs.)	5-speed manual	CVT	
4-door	2.0i: 2,955	2.0i: 3,032	
		Premium: 3,076	
		Limited: 3,109	
5-door	2.0i: 2,955	2.0i: 3,032	
	Sport Premium: 3,032	Premium: 3,076	
		Limited: 3,109	
		Sport Premium: 3,109	
		Sport Limited: 3,131	
	Note: Sport Premium has 5-speed manual transmission standard; all		
	other Premium and Limited trims have CVT standard.		
Interior Dimensions (in.)			
Headroom (f/r)	39.8/37.1 With moonroof: 37.2/37.1 (4D)		
	39.8/37.7 With moonroof: 37.2/37.7 (5D)		
Legroom (f/r)	43.5/35.4		
Hip room (f/r)	52.2/53.1		
Shoulder room (f/r)	55.6/54.2		
EPA passenger cabin volume	4-door: 96.9 (with moonroof: 93.4)		
. ,	5-door: 97.5 (with moonroof: 94.0)		
EPA interior volume	4-door: 108.9 w/ moonroof: 105.4		
(pass. cabin + cargo, cu. ft.)	5-door: 120.0 w/moonroof: 116.5		
Trunk liftover height	27.0		
EPA trunk volume, 4-door	12.0 cu. ft.		
Cargo volume, 5-door	Rear seats up/down: 22.5 cu. ft./52.4 cu. ft.		
Max. load floor length, 5-door	Rear seats up/down: 32.0/64.2 in.		
Fuel economy			
Transmission	5-speed manual	Lineartronic CVT	
EPA city / highway /	25/34/28	28/37/31	
combined	Sport: 24/33/28	Sport: 27/36/31	
Fuel tank capacity	14.5 gal.	1 00010 21700701	
i dei tank capacity	17.0 yai.		